

# ZOOMLION

## SCISSOR LIFTS

### ZS0407DC-Li



Comply with New Zealand latest Standard AS/NZ1418.10-2011

## HIGHLIGHTS

### High Performance

- ▶ Strong capacity of 240kg with high working efficiency
- ▶ Lightweight only 895KG
- ▶ Lithium-ion batteries features long service life that the running time increases by 30%, and could apply to -20°C cold working conditions, with 60 months warranty provided

### Cost Effectiveness

- ▶ Drawer type tray easy to service
- ▶ Modularized and unitized parts easy to maintenance

## FEATURES

### Standard Features

- ▶ Working height: 6.5m
- ▶ Platform elevated height: 4.5m
- ▶ Climbing up 30% degree slope

## WARRANTY

### Long Term Post Purchasing Services

- ▶ Up to 5 years structural warranty
- ▶ 2 years whole machine warranty

For all purchase enquiries please email:  
[info@lw-equipment.com](mailto:info@lw-equipment.com)



# ZOOMLION

## SCISSOR LIFTS ZS0407DC-Li

Comply with New Zealand latest Standard AS/NZ1418.10-2011

Size	Imperial	Metric
Work Height	21ft 4in	6.5m
A-Platform Height-Elevated	14ft 9in	4.5m
B-Platform Height-Stowed	3ft 1in	0.95m
C-Platform Length	4ft 3in	1.29m
D-Platform Width	2ft 4in	0.7m
Platform Extension	2ft	0.6m
E-Overall Height (Rails Up)	6ft 9in	2.05m
Overall Height (Rails Down)	5ft 7in	1.7m
F-Overall Length	4ft 9in	1.44m
G-Overall Width	2ft 6in	0.76m
H Wheelbase	3ft 5in	1.05m
I-Ground Clearance (Stowed)	2.4in	0.06m
J-Ground Clearance (Raised)	0.65in	0.017m

### Performance

Platform Capacity	530lb	240kg
Capacity on Deck Extension	220lb	100kg
Max. Number of Workers	2	
Drive Speed (Stowed)	2.5mph	4km/h
Drive Speed (Raised)	0.5mph	0.8km/h
Turning Radius (Inside)	1ft 4in	0.4m
Turning Radius (Outside)	5ft 3in	1.6m
Lifting Motor	24V/1.2KW	
Drive Motor	24V/2×0.45W	
Up/Down Time	23/25s	
Gradeability	30%(17°)	
Max. Working Slope (Lateral/Vertical)	1.5°/3°	
Control	Proportional Control	
Drive	Rear Wheels	
Brake	Rear Wheels	
Tire	Ø9in×3in	Ø230mm×80mm

### Power

Battery	80Ah Li-ion Battery
Charger	24V/15A

### Weight

Gross	1975lb	895kg
-------	--------	-------

